



ENCORE | 36", 48" HYDRO

- Positive-locking band and drum-style brakes on belt drives
- 0-5.5 mph forward speed
- 4-gallon fuel capacity
- Sharp-turning radius trimming ability
- 3-year limited parts and labor warranty
- 10-year limited deck warranty





ENCORE | 36", 48" HYDRO

ENGINE

Manufacturer:	Kawasaki FS481V
HP:	14.5HP*
Displacement:	603CC
Cooling:	Air cooled
Air Cleaning:	2 stage foam outter
Warranty:	2 year
Per SAE:	J1995*

DIMENSIONS

MODEL WB48K16H

Height:	41"
Length:	48.75"
Width:	42.375" 46" w/deflector up
Wheel Base:	47"
Wheel Track:	34" front 34" rear
Weight:	503 lbs

MODEL WB36K16H

Height:	41"
Length:	73"
Width:	36.5" 46" w/deflector up
Wheel Base:	35"
Wheel Track:	28" front 28" rear
Weight:	453 lbs

GENERAL

Fuel Capacity:	4 gallons
Front Tire:	4.10-3.5 x 4 (4 ply) smooth
Drive Tire:	16-6.5 x 8 (4 ply) turf saver
PTO:	Manual
Blade Tip Speed:	17,028 ft./min.

DRIVE SYSTEM

Type:	2 pump/2 motor Hydrostatic
Pumps:	Hydro-Gear
Wheel Motors:	Parker torq motors
Hydraulic Cooling:	Steel motor lines
Reservoir Capacity:	3 QT
Travel Speed:	0-5.5 mph
Steering:	Pistol-grip hand levers

DECKS

MODEL WB48K16H

Cutting Width:	48"
Cutting Height:	1"-4" in ¼" increments
Deck Lift:	Front caster
Blades:	3
Blade Length:	16" high lift
Spindles:	3
Deck Belts:	1
Construction:	10 ga. steel deck with reinforced 7 ga. top plate

MODEL WB36K16H

Cutting Width:	36"
Cutting Height:	1"-4" in ¼" increments
Deck Lift:	Front caster
Blades:	2
Blade Length:	18" high lift
Spindles:	2
Deck Belts:	1
Construction:	10 ga. steel deck with reinforced 7 ga. top plate